



# CHALLENGER Combi

## High Efficiency Combination Boiler and Domestic Water Heater

**HEAT .... and Hot Water .... TOGETHER in One Appliance**



- 94% AFUE
- Whisper Quiet
- Compact for Closet Applications
- ASME Stamped Heat Exchanger
- Compatible with Standard Glycol
- Direct Vent Sealed Combustion
- 2" & 3" PVC, CPVC, PP, SS Venting Options
- Concentric Venting Option
- Low NOx - 2012 SCAQMD Certified
- DHW - Low Lead Content Certified
- Multiple DHW Modes Allows User to Select Balance between Speed and Efficiency
- Unparalleled Reliability through Simplicity
- Simplified Design Eliminates Domestic Heat Exchanger, Circulator & Diverter Valve
- Integral Circulator
- 1 Year Limited Parts Warranty
- 10 Year Limited Heat Exchanger Warranty
- 5 & 10 Year Extended Warranty Options



**CONDENSES IN BOTH SPACE HEATING AND DOMESTIC HOT WATER MODES**



# Challenger Combi



## Technical Specifications

Model	CC 125 C
Input Modulation (MBH)	33 to 124
AFUE	94%
DOE Heating Capacity (MBH)	110
Net AHRI Rating (MBH)	96
Fuel	NG and LP
DHW flow rate at 70°F temp. rise (GPM)	3.0
DHW minimum flow rate (GPM)	0.5
DHW maximum temperature (F [C])	149 (65)
Maximum CH output temperature (F [C])	194 (90)
Cabinet Height (Inch)	28
Cabinet Width (Inch)	17 3/4
Cabinet Depth (Inch)	9 1/2
Weight (Lbs)	80

- The Challenger is certified both as a boiler and a water heater.
- Boiler Certified to ANSI Z21.13 / CSA 4.9
- Water Heater Certified to ANSI Z21.10.3 / CSA 4.3
- Water Heater Certified Low Lead Content Per NSF/ANSI 372.

## Standard Features

### Heat Exchanger

- Separate boiler and DHW copper waterways cast directly into the heat exchanger
- Cast aluminum heat exchanger with vertical flueways
- Compatible with Standard Glycol
- 10 year limited warranty

### Burner

- Stainless steel burner with woven fiber mesh
- Direct spark ignition
- Variable speed blower assembly
- Negative pressure regulated gas valve
- Propane conversion kit included

### Sensors

- Outdoor temperature
- Boiler supply temperature
- Boiler return temperature
- Flue temperature
- DHW temperature
- DHW flow switch
- Boiler system pressure

### Intake and Venting

- 2" & 3" Parallel venting (standard)
- Concentric venting (optional)
- PVC, CPVC, PP, SS material options

### Control

- Digital control displays in US customary or metric units
- Advanced modulating temperature control
- Outdoor reset
- Boiler low water protection
- Freeze protection
- High limit protection
- 3 DHW modes (Self learning ECO, standby, and on-demand)
- DHW priority
- DHW thermostatic mixing / anti-scald valve

### Electrical Connections

- 120V/60Hz Power supply
- Primary pump
- Thermostat
- Outdoor sensor

### Piping Connections

- EZ Install piping mounting bracket
- 3/4" NPT DHW inlet and outlet
- 1" NPT boiler supply and return
- 3/4" Condensate drain
- Integral circulator

Triangle Tube reserves the right to make product changes or improvements at any time without notice.



One Triangle Lane ■ Blackwood, NJ 08012

P 856 228 8881 f 856 228 3584 W [www.triangletube.com](http://www.triangletube.com)

